



# POREX® Porous PTFE Materials

## PM1015

PARAMETERS	VALUE	UNIT OF MEASUREMENT
AIR FLOW	≥ 3.2	l/hr/cm <sup>2</sup> ( $\Delta p$ 20mbar)
WATER INTRUSION PRESSURE	≥ 200	mbar
THICKNESS	1.50	mm ± 0.25

### ADDITIONAL INFORMATION

Airflow values determined from a 47mm  $\varnothing$  sample.

Can be Oleophobicity treated to Grade 8 by AATCC TM 118-1997.

#### Porex Technologies

500 Bohannon Road  
Fairburn, GA 30213 USA

E-mail: [infoPorex@porex.com](mailto:infoPorex@porex.com)

T. +1 770 9641421  
F. +1 770 9690954

#### Porex Technologies GmbH

Sales & Marketing Europe  
Strangenhäuschen 30  
52070 Aachen, Germany

E-mail: [infoPorex@porex.de](mailto:infoPorex@porex.de)

T. +49 241 9105250  
F. +49 241 91052526

#### Porex Technologies Ltd.

Merlin House  
Alness Point Business Park  
Alness, Ross-shire IV17 0UP  
Scotland, United Kingdom

E-mail: [infoPTFE@porex.com](mailto:infoPTFE@porex.com)

T. +44 1349 884060  
F. +44 1349 884076

#### Porex Technologies Sdn Bhd

Lot P.T. 74, Jalan Hulu Tinggi 26/6  
Seksyen 26, Sektor A  
Hicom Industrial Park  
40400 Shah Alam,  
Selangor, Malaysia

E-mail: [infoPorex@porex.com.my](mailto:infoPorex@porex.com.my)

T. +603 5191 3308  
F. +603 5192 3308